

P3500

Sourcewell
Formerly NAPA

Awarded Contract

Contract #080818RPM



In the background, an RPM227 snow blower in action in the Andes at Tudcum, Argentina.



**SINGLE STAGE
ROTARY FAN TYPE
DETACHABLE SNOW BLOWER**

P3500 – TECHNICAL SPECIFICATIONS



PERFORMANCE

- Capacity¹: Up to 5400 tons/hour
- Projection¹: Up to 39 m (130 ft)

DIMENSIONS

- Overall width: 2959 mm (116 ½ in.)
- Overall height: 2895 mm (114 in.)
- Working height: 1905 mm (75 in.)
- Weight: 7961 kg (17,550 lb) approx.

IMPELLER

- Diameter: 1740 mm (68 ½ in.)
- Blades: Six (6) blades, 6 mm (¼ in.) thick
- Rotation: 90° total
- Projection¹: Up to 39 m (130 ft)

STANDARD HYDRAULIC STEERING VANES

- Height: 2273 mm (89 ½ in.)

ENGINE

- Type: 403 kW (540 hp) Turbo Diesel engine
- Block heater: 3000 W

FUEL TANK

- Type: Steel
- Capacity: 415 L (109 gal)

HYDRAULIC SYSTEM

- Type: Hydraulic pump of 23 L/min (6 USGPM) directly mounted on engine auxiliary drive 19 L (5 gal)
- Capacity:

ELECTRICAL SYSTEM

- Alternator: 12 V, 150 A, sealed
- Batteries: Two (2) type 8D - 2000 CCA, maintenance free

DRIVELINE SYSTEM

- Clutch: Twin Disc, model SP-314
- Gear box: One (1) bevel gear box
- Lubrification: Oil bath
- Safety mechanism: One (1) set of shear bolts protects the fan

INSTRUMENT PANEL AND CONTROLS

- Model: Heavy duty control and display system PLUS +1 from Sauer Danfoss
- Controls:
 - ♦ One controller using a multiplex CAN communication
 - ♦ One high resolution grayscale LCD display of 2 in. x 4 ½ in.
 - ♦ One joystick with integrated functions
 - ♦ One key ignition switch

SKATES AND SCRAPER BLADES

- Quantity:
 - ♦ Two (2) external skates
 - ♦ Four (4) internal skates
- Type: Carbide skates
- Scraper blades:
 - ♦ Two (2) reversible scraper blades of 13 mm x 152 mm (½ in. x 6 in.)
 - ♦ One (1) non-reversible scraper blade of 13 mm x 178 mm (½ in. x 7 in.)

OPTIONAL EQUIPMENT

- 256 color LCD screen of 3 ⅜ in. x 5 ¾ in.
- Carbide chrome 60Rc (drum)
- Low coolant level alarm
- Residential Cowl muffler
- Wireless control system
- Wireless emergency engine shutdown system

¹Depending on snow conditions.

www.rpmtechgroup.com



R.P.M. TECH INC.

2220 Michelin Street
Laval QC H7L 5C3 CANADA

Tel.: +1 450.687.3280

Toll free: 1.800.631.9297 (North America)

Email: info@rpmtechgroup.com

Dealer

2018.10 ~ RPM Tech Inc. reserves the right to change or discontinue any designs, specifications, features, models or accessories shown or indicated without notice.