

RPM36R

Two Stage Loader-Mounted Snow Blower

▶ Up to 3,000 tons/hour

▶ High-speed ribbon type

▶ High-performance transmission

▶ Tier 4 Stage 5 engine

▶ Heavy-duty construction



Watch Video



Actual product may vary from photos due to continuous product enhancement



Power and Speed

The RPM36R is a two phase, ribbon type snow blower providing an impressive snow-clearing capacity of 3,000 tons/hour. With its 914 mm (36 in.) diameter ribbon and oversized impeller, the RPM36R can easily manage large snowfalls and major snow accumulations. This self-contained model is designed to be front-end mounted on a medium to large size loader.

The RPM36R is equipped with an efficient and rugged powertrain. The high-performance transmission system is designed to use maximum engine's power while minimizing energy losses and maintenance.

A Powerful Engine

The RPM36R is powered by a 225 kW (300 hp) dual certified Tier 4 Stage 5 Diesel engine equipped with particle post-treatment technology allowing fast engine recovery.

- Uncompromising performance
- Fuel efficient
- Quiet



A High-Performance Transmission

Engineered with as few components as possible, the RPM36R transmission is dependable and transfers maximum power from the engine allowing an outstanding snow-clearing capacity of 3,000 tons/hour. The transmission relies on an oversized gearbox, withstanding hard work and minimizing energy losses.

- Highly reliable
- Optimal power transfer
- Reduce spare parts dependency
- Lower maintenance costs




Belt Drive System

The RPM36R belt drive system provides many advantages over a chain drive as well as greater shock resistance.

- Transfers up to 98% of engine power
- Longer service life
- No oil bath
- No risk of leaks
- Reduces replacement of shear bolts
- Minimizes interruptions and down time

RPM36R





An Effective Impeller

With its large impeller casing featuring an unrestricted intake of 972 mm (38 ¼ in.) in diameter, more snow is fed to the impeller blades thus better productivity.

- Blows a higher volume of snow
- Makes full use of engine power



Emergency Clutch Engagement

In the event of a clutch failure, a lever allows for its manual activation to let you finish the job.

Easy Maintenance

The tilt-up engine cowling, swing doors grease zerks, and well-thought-out mechanical design provide easy access to main components or parts requiring regular maintenance, such as:

- Oil and fuel filters
- Hydraulic oil tank
- Radiator
- Shear bolts
- Gear box



The Most Rugged Frame

The triangular frame design composed of four (4) oversized beams, two (2) on each side, maintains the structure integrity during hard work and makes it more resistant to impacts. RPM Tech's snow blowers are built to last!



Intuitive Operation

The color display screen provides the operator with a clear view of the blower's operating parameters. Optimized for all lighting conditions, the screen automatically adjusts and switches between day and night display modes. All functions are easily controlled with an intuitive joystick.



The RPM36R is ideal for:

- Municipalities
- National park roads
- Mountain passes
- Regional airports

RPM Tech Advantages

- Proven performance and service life
- Designed for extended periods of hard use
- Heavy-duty construction resists deformation
- Engine application audited and approved by Caterpillar®
- Weather-resistant electrical components
- More than 55 years of experience designing and manufacturing snow-removal equipment

Summary Technical Specifications – RPM36R

Up to 3,000 tons/hour capacity¹

Casting¹: Up to 46 m (150 ft)

Clears fresh, heavy, and hard-packed snow

DIMENSIONS AND WEIGHT

- Cutting width: 2795 mm (110 in.) with bolted steering guides
- Overall height: 3442 mm (135.5 in.) telescopic chute retracted
- Overall length: 2565 mm (101 in.) with bolted steering guides and without coupler
- Working height: 1321 mm (52 in.)

- Weight (approx.): 4763 kg (10,500 lb) approx. with full fuel tank, without coupler and options

RIBBON

- One (1) 914 mm (36 in.) diameter serrated ribbon made of wear resistant and high strength Hardox® steel

TELESCOPIC CHUTE

- Adjustable working height: from 3442 to 3899 mm (135.5 to 153.5 in.)
- Casting distance¹: From 1 to 16 m (3 to 50 ft)

IMPELLER AND IMPELLER CASING

- 940 mm (37 in.) diameter oversized impeller
- Five (5) bolted concave blades
- Impeller casing:
 - Diameter: 972 mm (38 ¾ in.)
 - Depth: 349 mm (13 ¾ in.)
 - Volume of 268.6 liters (71 usgal)
 - 145° rotation allowing side casting on either side
- Casting¹: Up to 46 m (150 ft) through the impeller housing chute

ENGINE

- 225 kW (300 hp) C7.1 Caterpillar® dual certified Tier 4 Stage 5, turbocharged Diesel engine
- Winter starting aid: 1000 W block heater and glow plugs

TRANSMISSION

- A belt drive system with **no** oil bath
- One (1) right angle spiral bevel gear box
- Two (2) drive shafts providing power to the ribbon and impeller
- Two (2) sets of shear bolt protect the gear box and transmission shaft

CLUTCH

- Twin Disc® clutch, actuated by cabin controlled hydraulic cylinder
- Greasing system easily accessible

FUEL TANK

- 300 L (79 gal) steel tank

CHASSIS

- Fully welded, sturdy steel construction

ELECTRICAL SYSTEM

- All electrical components are in a waterproof box

CONTROLS AND INSTRUMENTATION

- Heavy-duty Sauer Danfoss PLUS+1 control system
- LCD color display screen, high day/night visibility
- Joystick with integrated functions and ignition key switch

SKATES AND SCRAPER BLADES

- Eight (8) Trimay® skates totalizing 3935 cm² (610 in²) of wear surface
- Two (2) 44W steel reversible scraper blades

ACCESSORIES INCLUDED

- DEF tank heater

OPTIONAL EQUIPMENT (SHORT LIST)

- Wireless remote control system
- Arctic lubrication kit for constant temp. below -25°C (-13°F)
- Battery and/or hydraulic oil heater
- Work and/or chute lighting (LED or halogen)
- Carbide bottom cutting edge
- Complete female quick coupler system

Tenco inc. reserves the right to modify or discontinue any design, specifications, characteristics, model, or accessory without notice.



¹ Depending on snow conditions

Contact your representative for full details

Tel: +1 450.687.3280

1 800.631.9297
(North America)

info@rpmtechgroup.com

RPM Tech, a Trademark of Tenco Inc.,

A Member of

